


Access



AGRICULTURE

YOUR EMBEDDED MECHATRONIC SOLUTIONS




Tel: 1.800.567.1041
Sales: 905.274.2555

Email: Sales@AccessControlSales.com
Web: www.AccessControlSales.com


ACCESS
CONTROL SALES

161 Lakeshore Rd. E.
Mississauga ON.
L5G 4T9

OUR CATALOGS




ADR
TRANSPORT OF
DANGEROUS GOODS



CONSTRUCTION



GOODS
TRANSPORT



LIFTING
& HANDLING EQUIPMENT



MARINE




PASSENGERS
TRANSPORT



QUARRYING
& MINING



SPECIAL VEHICLES
& MACHINERY



CONTENTS

BATTERY MASTER SWITCH ELECTRICAL CONTROL	3
BATTERY MASTER SWITCH MANUAL CONTROL	13
POWER RELAY	27
SWITCH AND BUTTON	29
SPARE PARTS	33

AGRICULTURE



BATTERY MASTER SWITCH
ELECTRICAL CONTROL

BISTABLE		
SINGLE POLE		
	S220	4
	S250	5
	S260	7



BATTERY MASTER SWITCH - ELECTRICAL CONTROL BISTABLE - SINGLE POLE

S220 SERIES



GLOBAL PRODUCT



203105

GENERAL CHARACTERISTICS

IP67
IPX9K

+85 °C
-40 °C

PBT
glass
filled

700g

M8

Continuous rating 200 A

Overload 800 A (10 s)

Temporization 15 s (wiring option)

VERSIONS

GROUND or POSITIVE CUT-OFF

12 V or 24 V

PRODUCT SELECTION

P/N	RATED VOLTAGE	POLARITY	TERMINALS		AUXILIARY CIRCUIT	
			LENGTH	MATERIAL	TYPE	CONTINUOUS RATING
203105	24 V	+ CUT-OFF	6 mm	Silver plated copper	LED control	12 W (0,5 A)
203106	12 V	+ CUT-OFF	6 mm	Silver plated copper	LED control	12 W (1 A)
203254	24 V	GND CUT-OFF	6 mm	Silver plated copper	LED control	12 W (0,5 A)
203255	12 V	GND CUT-OFF	6 mm	Silver plated copper	LED control	12 W (1 A)

On request: specific technical demand can be studied

CONTROL SWITCH (see «Switch and button» section)



ON-OFF SWITCH

S701 SERIES
2-Pin ISO 15170 / DIN 72585

250254

To use with:

All the S220 SERIES

ACCESSORIES (see «Spare parts» section)

CABLING KIT

713 SERIES
4-Pin Superseal connector &
wire

250025

BUSBAR

900 SERIES
3 M8 terminals (washers & nuts
included)

203213



300 A

BATTERY MASTER SWITCH - ELECTRICAL CONTROL

BISTABLE - SINGLE POLE

S250 SERIES

BATTERY SWITCH
ELECTRICAL CONTROL

GLOBAL PRODUCT



202319

GENERAL CHARACTERISTICS

IP65

+85 °C
-40 °CPBT
Reinforced

1000 g

M10

Continuous rating 300 A

Overload 1500 A (15 s)

VERSIONS

MASTER or SLAVE

GROUND or POSITIVE CUT-OFF

12 V or 24 V

OPTIONS

Auxiliary circuit

Temporization

Low Voltage Monitoring (LVM)

BATTERY SWITCH
MANUAL CONTROL

POWER RELAY



202976



202638

SWITCH AND BUTTON

ACCESSORIES AND
SPARE PARTS

CONTROL SWITCHES (see «Switch and button» section)

PUSH BUTTON SWITCH

S700 SERIES
2-Pin ISO 15170 / DIN 72585

202170

To use with:

See product selection table



ON-OFF SWITCH

S701 SERIES
2-Pin ISO 15170 / DIN 72585

250254

To use with:

See product selection table



300 A

BATTERY MASTER SWITCH - ELECTRICAL CONTROL BISTABLE - SINGLE POLE

S250 SERIES

PRODUCT SELECTION

MASTER										
P/N	VOLT	TERMINALS		POLARITY	AUXILIARY CIRCUIT	LVM	TEMPORIZATION	CONTROL TYPE	CONNECTION	OPTION
		LENGTH	MATERIAL							
202301	12 V	13 mm	Copper	+ CUT-OFF	-	-	-	2 push buttons	3 wires	-
202310	24 V	10 mm	Silver plated copper	+ CUT-OFF	Relay D+	-	-	ON-OFF	4 wires	-
202311	12 V	10 mm	Silver plated copper	+ CUT-OFF	Relay D+	-	-	ON-OFF	4 wires	-
202316	24 V	10 mm	Silver plated copper	+ CUT-OFF	Relay D+	-	-	2 push buttons	4 wires	-
202317	12 V	10 mm	Silver plated copper	+ CUT-OFF	Relay D+	-	-	2 push buttons	4 wires	-
202319	24 V	10 mm	Silver plated copper	+ CUT-OFF	D+	-	-	ON-OFF	4-Pin, DIN connector	-
202595	12 V	10 mm	Silver plated copper	+ CUT-OFF	Relay control output for D+	60 sec	-	Monostable	7-Pin, DIN connector	-
202597	24 V	10 mm	Silver plated copper	+ CUT-OFF	Relay control output for D+	60 sec	-	Monostable	7-Pin, DIN connector	-
202636	12 V	10 mm	Silver plated copper	+ CUT-OFF	D+	-	-	ON-OFF	4-Pin, DIN connector	-
202637	12 V	10 mm	Silver plated copper	+ CUT-OFF	Relay control output for D+	5 min	-	Monostable	7-Pin, DIN connector	-
202639	24 V	10 mm	Silver plated copper	+ CUT-OFF	Relay control output for D+	5 min	-	Monostable	7-Pin, DIN connector	-
202698	12 V	10 mm	Silver plated copper	+ CUT-OFF	D+	-	30 s	ON-OFF	4 wires	-
202800	24 V	10 mm	Silver plated copper	GND CUT-OFF	Relay control output 200 mA	-	30 s	ON-OFF	5-Pin, Superseal connector	-
202976	12 V	10 mm	Silver plated copper	GND CUT-OFF	-	-	30 s	ON-OFF	2-Pin, Superseal connector	-
203035	24 V	10 mm	Silver plated copper	+ CUT-OFF	-	-	5 min	ON-OFF	2-Pin, Superseal connector	-

SLAVE										
P/N	VOLT	TERMINALS		POLARITY	AUXILIARY CIRCUIT	LVM	TEMPORIZATION	CONTROL TYPE	CONNECTION	
		LENGTH	MATERIAL							
202664	12 V	10 mm	Silver plated copper	GND CUT-OFF	-	-	-	ON-OFF	2 wires	
202665	24 V	10 mm	Silver plated copper	GND CUT-OFF	-	-	-	ON-OFF	2 wires	

On request: specific technical demand can be studied

ACCESSORIES (see « Spare parts» section)

CABLING KIT

713 SERIES
2-Pin Superseal connector & wire

250351

713 SERIES
5-Pin Superseal connector & wire

250350

713 SERIES
4-Pin DIN connector

250333

713 SERIES
7-Pin DIN connector

250352

TERMINAL INSULATION CAP

900 SERIES
Red

201010

900 SERIES
Black

202499

TERMINAL HEIGHTENED

900 SERIES

200588

S260 SERIES



GLOBAL PRODUCT



202710

GENERAL CHARACTERISTICS

IP67 IPX9K	+85 °C -40 °C	PBT glass filled	850g	M10
---------------	------------------	---------------------	------	-----

Continuous rating 300 A
Overload 1500 A (15 s)
Temporization 2.5 s
Positive Cut-off

VERSIONS

12 V or 24 V

PRODUCT SELECTION

P/N	VOLT	TERMINALS		AUXILIARY CIRCUIT		TEMPORIZATION	CONNECTION	CONTROL TYPE
		LENGTH	MATERIAL	TYPE	CONTINUOUS RATING			
202710	24 V	12 mm	Silver plated copper	D+	300 mA	2.5 s	7-Pin DIN type connector	ON-OFF
202712	12 V	12 mm	Silver plated copper	D+	300 mA	2.5 s	7-Pin DIN type connector	ON-OFF

On request: specific technical demand can be studied

CONTROL SWITCH (see «Switch and button» section)



ON-OFF SWITCH

S701 SERIES 202556
4-Pin ISO 15170 / DIN 72585

To use with:

All the S260 SERIES

ACCESSORIES (see «Spare parts» section)

CABLING KIT

713 SERIES 250352
7-Pin DIN connector with 3m
length cable

TERMINAL INSULATION CAP

900 SERIES 201010
Red

900 SERIES 202499
Black

TERMINAL HEIGHTENED

900 SERIES 200588



BATTERY MASTER SWITCH ELECTRICAL CONTROL



250 A

S200

MONOSTABLE

SINGLE POLE

10



250 A

BATTERY MASTER SWITCH - ELECTRICAL CONTROL

MONOSTABLE - SINGLE POLE

S200 SERIES



GLOBAL PRODUCT



GENERAL CHARACTERISTICS

IP65



Zinc alloy

UNTIL
1400 gM10
M12

Continuous rating 250 A

Overload 1800 A (60 s)

Ground or positive Cut-off

VERSIONS

12 V or 24 V

OPTIONS

Fixation adapter

Protection diode

Electrical load switching

202136



200735



200358

CONTROL SWITCH (see «Switch and button» section)




ON-OFF SWITCH

S701 SERIES 250254
2-Pin ISO 15170 / DIN 72585

To use with:

All the S200 SERIES



BATTERY MASTER SWITCH - ELECTRICAL CONTROL MONOSTABLE - SINGLE POLE

S200 SERIES

BATTERY SWITCH
ELECTRICAL CONTROL

BATTERY SWITCH
MANUAL CONTROL

POWER RELAY

SWITCH AND BUTTON

ACCESSORIES AND
SPARE PARTS

PRODUCT SELECTION

P/N	VOLT	FINISH	WEIGHT	TERMINALS				AUXILIARY CIRCUIT			OTHER
				SIZE	LENGTH	MATERIAL	SPACER ON TERMINALS	TYPE	CONNECTION	ACCESSORIES	
200358	12 V	Black	1260 g	M10	8 mm	Copper	No	-	-	-	«U» shape bracket
200359	24 V	Black	1260 g	M10	8 mm	Copper	No	-	-	-	«U» shape bracket
200439	24 V	Metallic	960 g	M10	7 mm	Copper	Yes	Normally open	2 x M5	-	-
200686	12 V	Metallic	960 g	M10	7 mm	Copper	No	-	-	-	-
200735	12 V	Metallic	960 g	M10	7 mm	Copper	No	D+	2 x M5	Shunt	-
200819	24 V	Metallic	1400 g	M10 + M12	7 mm	Copper	No	-	-	-	«U» shape bracket + blade adapter plate
200820	24 V	Metallic	960 g	M10	7 mm	Copper	No	-	-	-	-
200822	12 V	Metallic	1400 g	M10 + M12	7 mm	Copper	No	-	-	-	«U» shape bracket + blade adapter plate
200824	24 V	Metallic	1400 g	M10 + M12	7 mm	Copper	No	D+	2 x M5	Shunt	«U» shape bracket + blade adapter plate
201217	24 V	Metallic	1260 g	M10	14 mm	Copper	Yes	-	-	-	«U» shape bracket
201245	24 V	Metallic	960 g	M10	7 mm	Copper	Yes	D+	2 x M5	Shunt	-
201766	24 V	Metallic	960 g	M10	22 mm	Copper	No	-	-	-	-
201926	24 V	Metallic	960 g	M10	14 mm	Copper	Yes	-	-	-	-
202072	24 V	Metallic	960 g	M10	7 mm	Copper	Yes	D+	2 x M5	Shunt	Protection diode
202136	12 V	Metallic	960 g	M10	7 mm	Copper	Yes	D+	2 x M5	Shunt	Protection diode
202159	24 V	Metallic	960 g	M10	22 mm	Copper	No	-	-	-	Protection diode

On request: specific technical demand can be studied

ACCESSORIES (see «Spare parts» section)

TERMINAL HEIGHTENED

900 SERIES

200588

TERMINAL INSULATION CAP

900 SERIES
Red

201010

900 SERIES
Black

202499



BATTERY MASTER SWITCH MANUAL CONTROL



S190

14

DOUBLE POLE



300 A

BATTERY MASTER SWITCH - MANUAL CONTROL

DOUBLE POLE

S190 SERIES



GLOBAL PRODUCT



200019

GENERAL CHARACTERISTICS

IP65

+85 °C
-40 °CZinc
alloyuntil
1200g

M10

Continuous rating until 300 A

Overload 2500 A (5 s)

Ground or positive Cut-off

OPTIONS

Auxiliary circuit

PRODUCT SELECTION

P/N	CONTINUOUS RATING	WEIGHT	HANDLE		TERMINALS			AUXILIARY CIRCUIT			
			TYPE	COLOR AND MATERIAL	LENGTH	MATERIAL	SPACER OF TERMINALS	TYPE	ACCESSORIES	CONTINUOUS RATING	CONNECTION
200014	250 A	1100 g	Fixed / 2 positions	Red thermoplastic	6 mm	Copper	Yes	D+	Shunt	10 A	1 x M6
200015	250 A	1100 g	Fixed / 2 positions	Red thermoplastic	12 mm	Copper	No	-	-	-	-
200018	250 A	1100 g	Fixed / 2 positions	Red thermoplastic	6 mm	Copper	Yes	Normally open	Shunt	10 A	1 x M6
200019	250 A	1100 g	Fixed / 2 positions	Red thermoplastic	6 mm	Copper	Yes	Normally open	-	10 A	2 x M6
200034	250 A	1100 g	Fixed / 2 positions	Red thermoplastic	15 mm	Copper	No	-	-	-	-
200232	250 A	1200 g	Fixed / 2 positions	Red thermoplastic	6 mm	Copper	Yes	-	-	-	-
200913	250 A	1110 g	«L» shape, removable in ON and OFF positions	Red thermoplastic	12 mm	Copper	No	-	-	-	-
201148	250 A	1150 g	High, removable in ON and OFF positions	Red thermoplastic	6 mm	Copper	Yes	-	-	-	-
201544	250 A	1100 g	Removable in ON and OFF positions	Red thermoplastic	12 mm	Copper	No	-	-	-	-
203098	300 A	1100 g	Fixed / 2 positions	Red thermoplastic	12 mm	Tin-plated copper	Yes	-	-	-	-

On request: specific technical demand can be studied



300 A

BATTERY MASTER SWITCH - MANUAL CONTROL DOUBLE POLE

S190 SERIES

BATTERY SWITCH
ELECTRICAL CONTROL

BATTERY SWITCH
MANUAL CONTROL

POWER RELAY

SWITCH AND BUTTON

ACCESSORIES AND
SPARE PARTS

ACCESSORIES (see Spare parts)

HANDLE

901 SERIES
For P/N 200913

200392

901 SERIES
For P/N 201148

200929

901 SERIES
For P/N 201544

201134

TERMINAL INSULATION CAP

900 SERIES
Red

201010

900 SERIES
Black

202499

TERMINAL HEIGHTENED

900 SERIES

200588



BATTERY MASTER SWITCH MANUAL CONTROL

SINGLE POLE

	S9	18
	S10	19
	S20	20
	S30	22
	S50	23
	S100	24

BATTERY SWITCH
MANUAL CONTROL

POWER RELAY

SWITCH AND BUTTON

ACCESSORIES AND
SPARE PARTS

BATTERY SWITCH
ELECTRICAL CONTROL



100 A

BATTERY MASTER SWITCH - MANUAL CONTROL

SINGLE POLE

S9 SERIES



GLOBAL PRODUCT



202373

GENERAL CHARACTERISTICS

IP43

+80 °C
-40 °CAnodized
Aluminium

200 g

M10

Continuous rating 100 A

Overload 500 A (10 s)

Ground or positive Cut-off

PRODUCT SELECTION

P/N	HANDLE		TERMINALS	
	TYPE	COLOR AND MATERIAL	LENGTH	MATERIAL
202373	Key removable in ON and OFF position	Red thermoplastic and steel key	10 mm	Copper

On request: specific technical demand can be studied

ACCESSORIES (see «Spare parts» section)

TERMINAL INSULATION CAP

900 SERIES 201010
Red

900 SERIES 202499
Black

TERMINAL HEIGHTENED

900 SERIES 200588

PROTECTION CAPS

900 SERIES 201898

S10 SERIES



GLOBAL PRODUCT



GENERAL CHARACTERISTICS

IP67
IP41

+80 °C
-40 °C

PPO
glass filled

150g

M10

Continuous rating 100 A

Overload 500 A (10 s)

Ground or positive Cut-off

VERSIONS

IP67 or IP41

OPTIONS

Homologation

PRODUCT SELECTION

P/N	PROTECTION DEGREE	HOMOLOGATION	TERMINALS MATERIAL	TYPE OF HANDLE	ACCESSORIES
201767	IP67	ISO 8846 / ISO 10133	Copper	Removable in OFF position	-
201768	IP67	ISO 8846 / ISO 10133	Copper	Removable in OFF position	Chain
201831	IP67	ISO 8846 / ISO 10133	Tin-plated copper	Removable in OFF position	Tin-plated nuts
202365	IP41	-	Copper	Removable in OFF position	-
203201	IP67	ISO 8846 / ISO 10133	Copper	Removable in OFF position	Chain and protection cap

On request: specific technical demand can be studied

ACCESSORIES

CHAIN

900 SERIES 200894

RUBBER PROTECTION

900 SERIES 203243

HANDLE

901 SERIES 202474
For P/N 201767 - 201768 - 201831 - 202365 - 203201

TERMINAL INSULATION CAP

900 SERIES 201010
Red

900 SERIES 202499
Black

TERMINAL HEIGHTENED

900 SERIES 200588



BATTERY MASTER SWITCH - MANUAL CONTROL SINGLE POLE

S20 SERIES



GLOBAL PRODUCT



200057

GENERAL CHARACTERISTICS



Continuous rating 150 A

Overload 1000 A (5 s)

VERSIONS

GROUND or POSITIVE CUT-OFF

OPTIONS

Homologation

Auxiliary circuit



200048



200801



BATTERY MASTER SWITCH - MANUAL CONTROL

SINGLE POLE

S20 SERIES

BATTERY SWITCH
ELECTRICAL CONTROL

BATTERY SWITCH
MANUAL CONTROL

POWER RELAY

SWITCH AND BUTTON

ACCESSORIES AND
SPARE PARTS

PRODUCT SELECTION

P/N	PROTECTION DEGREE	FINISH	HANDLE		HOMOLOGATION	POLARITY	TERMINALS		AUXILIARY CIRCUIT		OPTION
			TYPE	COLOR AND MATERIAL			LENGTH	MATERIAL	TYPE	TERMINALS SIZE	
200021	IP54	Metallic	Fixed / 2 positions	Red thermoplastic	-	+ CUT-OFF	4 mm	Copper	Normally open	6.35 PIN	-
200023	IP65	Metallic	Fixed / 2 positions	Black thermoplastic	ISO 8846	GND CUT-OFF	4 mm	Copper	-	-	-
200048	IP65	White	Fixed / 2 positions	Red thermoplastic	ISO 8846 / ISO 10133	+ CUT-OFF	4 mm	Copper	-	-	-
200049	IP65	White	Fixed / 2 positions	Black thermoplastic	ISO 8846	GND CUT-OFF	4 mm	Copper	-	-	-
200057	IP40	Metallic	Fixed / 2 positions	Metallic	-	GND or + CUT-OFF	4 mm	Copper	Changeover switch	6.35 PIN	-
200060	IP67	Metallic	Fixed / 2 positions	Metallic	ISO 8846 / ISO 10133	GND or + CUT-OFF	4 mm	Copper	-	-	-
200061	IP67	Metallic	Removable in OFF position	Metallic	ISO 8846 / ISO 10133	GND or + CUT-OFF	4 mm	Copper	-	-	-
200801	IP67	Metallic	Removable in OFF position	Metallic	ISO 8846 / ISO 10133	GND or + CUT-OFF	4 mm	Copper	-	-	Red protection cap
201363	IP65	Metallic	Fixed / 2 positions	Red thermoplastic	ISO 8846 / ISO 10133	+ CUT-OFF	4 mm	Copper	-	-	-
201540	IP65	Metallic	Fixed / 2 positions	Red thermoplastic	ISO 8846 / ISO 10133	+ CUT-OFF	13 mm	Copper	-	-	-
201543	IP65	Metallic	Fixed / 2 positions	Black thermoplastic	ISO 8846	GND CUT-OFF	13 mm	Copper	-	-	-
202740	IP67	Metallic	Removable in OFF position	Metallic	ISO 8846 / ISO 10133	GND or + CUT-OFF	13 mm	Copper	-	-	-
203185	IP67	Metallic	Removable in OFF position	Metallic	ISO 8846 / ISO 10133	GND or + CUT-OFF	4 mm	Copper	-	-	Black protection cap

On request: specific technical demand can be studied

ACCESSORIES

HANDLE

901 SERIES

For P/N 200061 - 200801 - 202740

200700

901 SERIES

For P/N 203185

203186

TERMINAL INSULATION CAP

900 SERIES

Red

201010

900 SERIES

Black

202499

TERMINAL HEIGHTENED

900 SERIES

200588



BATTERY MASTER SWITCH - MANUAL CONTROL

SINGLE POLE

S30 SERIES



GLOBAL PRODUCT



GENERAL CHARACTERISTICS

IP68
IPX9K

+85 °C
-40 °C

PA66
glass filled

190g

M10

Continuous rating 275 A

Overload 1250 A (10 s)

Ground or positive Cut-off

PRODUCT SELECTION

P/N	FINISH	HANDLE		HOMOLOGATION	TERMINALS	
		TYPE	COLOR AND MATERIAL		LENGTH	MATERIAL
203250	Yellow	Removable in 3rd position «Padlock»	Red thermoplastic	ISO 8846 / ISO 10133	8,5 mm	Tin-plated copper
203253	Black	Removable in 3rd position «Padlock»	Yellow thermoplastic	ISO 8846	8,5 mm	Tin-plated copper
203260	White	Removable in 3rd position «Padlock»	Red thermoplastic	ISO 8846 / ISO 10133	8,5 mm	Tin-plated copper
203380	Black	Removable in 3rd position «Padlock»	Red thermoplastic	ISO 8846 / ISO 10133	8,5 mm	Tin-plated copper

On request: specific technical demand can be studied

ACCESSORIES

HANDLE

901 SERIES
Red 203085

901 SERIES
Yellow 203252

TERMINAL INSULATION CAP

900 SERIES
Red 201010

900 SERIES
Black 202499

INSULATION PLATE

900 SERIES
Yellow 203249

900 SERIES
White 203259

900 SERIES
Black 203088



BATTERY MASTER SWITCH - MANUAL CONTROL

SINGLE POLE

S50 SERIES



BATTERY SWITCH
ELECTRICAL CONTROL

BATTERY SWITCH
MANUAL CONTROL

POWER RELAY

SWITCH AND BUTTON

ACCESSORIES AND
SPARE PARTS

GLOBAL PRODUCT



GENERAL CHARACTERISTICS

IP68	+85 °C -40 °C	Zinc alloy	500g	M10
------	------------------	------------	------	-----

Continuous rating 300 A

Overload 3000 A (5 s)

Ground or positive Cut-off

VERSIONS

FIXED or REMOVABLE HANDLE

PRODUCT SELECTION

P/N	FINISH	HANDLE		TERMINALS		POWER DROP	OPTION	LOCKABLE
		TYPE	COLOR AND MATERIAL	LENGTH	MATERIAL			
200027	Metallic	Removable in OFF position	Metallic	16 mm	Copper	50 mV max at 300 A	-	-
200028	Metallic	Removable in OFF position	Metallic	16 mm	Copper	50 mV max at 300 A	Chain	-
201900	Metallic	Removable in OFF position	Metallic	16 mm	Copper	50 mV max at 300 A	Chain + red protection cap	-
202500	Metallic	Removable in OFF position	Red metallic	16 mm	Copper	50 mV max at 300 A	Chain	-
203235	Black	Fixed / 2 positions	Red thermoplastic	16 mm	Tin-plated copper		-	-

On request: specific technical demand can be studied

ACCESSORIES

HANDLE		TERMINAL INSULATION CAP	
901 SERIES For P/N 200027	200993	900 SERIES Red	201010
901 SERIES For P/N 200028 - 201900	202633	900 SERIES Black	202499
901 SERIES For P/N 202500	202841		



250 A

BATTERY MASTER SWITCH - MANUAL CONTROL SINGLE POLE

S100 SERIES



GLOBAL PRODUCT



200008

GENERAL CHARACTERISTICS

IP66

+85 °C
-40 °C

Zinc
alloy

until
650g

M10

Continuous rating 250 A

Overload 2500 A (5 s)

VERSIONS

GROUND or POSITIVE CUT-OFF

FIXED or REMOVABLE HANDLE

OPTIONS

Auxiliary circuit



200010



200033



BATTERY MASTER SWITCH - MANUAL CONTROL SINGLE POLE

S100 SERIES

BATTERY SWITCH
ELECTRICAL CONTROL

BATTERY SWITCH
MANUAL CONTROL

POWER RELAY

SWITCH AND BUTTON

ACCESSORIES AND
SPARE PARTS

PRODUCT SELECTION

P/N	FINISH	HANDLE		POLARITY	TERMINALS		AUXILIARY CIRCUIT			OPTION
		TYPE	COLOR AND MATERIAL		LENGTH	MATERIAL	TYPE	CONTINUOUS RATING	CONNECTION	
200000	Metallic	Fixed / 2 positions	Red thermoplastic	GND or + CUT-OFF	20 mm	Copper	Normally open	10 A	1 x 6.35 + shunt	
200001	Metallic	Fixed / 2 positions	Red thermoplastic	GND CUT-OFF	7 mm	Copper	D+	10 A	1 M6 + shunt	
200004	Metallic	Removable in OFF position	Red thermoplastic	GND or + CUT-OFF	7 mm	Copper	D+	10 A	1 M6 + shunt	
200006	Metallic	Fixed / 2 positions	Red thermoplastic	GND or + CUT-OFF	20 mm	Copper	Normally open	10 A	2 x 6.35	
200007	Metallic	Fixed / 2 positions	Red thermoplastic	GND or + CUT-OFF	21 mm	Copper	Normally open	10 A	1 x 6.35 + shunt	Protection flap
200008	Metallic	Fixed / 2 positions	Red thermoplastic	GND or + CUT-OFF	10 mm	Copper	-	-	-	
200010	Black	Fixed / 2 positions	Red thermoplastic	GND CUT-OFF	10 mm	Copper	-	-	-	
200011	Metallic	Removable in OFF position	Red thermoplastic	GND or + CUT-OFF	10 mm	Copper	-	-	-	
200012	Metallic	Fixed / 2 positions	Red thermoplastic	GND or + CUT-OFF	13 mm	Copper	-	-	-	Protection flap
200031	Metallic	Fixed / 2 positions	Red thermoplastic	GND or + CUT-OFF	13 mm	Copper	Normally open	10 A	1 x 6.35 + shunt	
200032	Metallic	Fixed / 2 positions	Red thermoplastic	GND or + CUT-OFF	8 mm	Copper	Normally open	10 A	2 x 6.35	Rubber protection
200033	Metallic	Fixed / 2 positions	Red thermoplastic	GND or + CUT-OFF	13 mm	Copper	-	-	-	
200043	Metallic	Fixed / 2 positions	Red metallic	GND or + CUT-OFF	10 mm	Copper	-	-	-	
201437	Metallic	Fixed / 2 positions	Red thermoplastic	GND or + CUT-OFF	20 mm	Copper	D+	10 A	2 x 6.35	Rubber protection
202574	Metallic	Fixed / 2 positions	Red thermoplastic	GND or + CUT-OFF	10 mm	Copper	-	-	-	Rubber protection

On request: specific technical demand can be studied

ACCESSORIES

HANDLE

901 SERIES

For P/N 200004 - 200011

200929

TERMINAL INSULATION CAP

900 SERIES

Red

201010

900 SERIES

Black

202499

AGRICULTURE



POWER RELAY NORMALLY OPEN



100 A

POWER RELAY
NORMALLY OPEN

S500 SERIES



GLOBAL PRODUCT



GENERAL CHARACTERISTICS

IP65



Steel

550g



Continuous rating 100 A

Overload until 600 A (5 s)

Ground or positive Cut-off

VERSIONS

12 V or 24 V

0.4 A to 0.7 A current consumption

PRODUCT SELECTION

P/N	SECONDARY CONTROL	VOLT	FINISH	OVERLOAD	TERMINALS		CONTROL CIRCUIT CONNECTION	CURRENT CONSUMPTION	TEMPORARY USE (4h max)
					LENGTH	MATERIAL			
201470	-	24 V	Black	500 A (5 s)	6 mm	Copper	2 x M5 studs	0.6 A	130 A
201480	-	12 V	Black	500 A (5 s)	6 mm	Copper	2 x M5 studs	0.5 A	150 A
201570	Manual control	24 V	Black	500 A (5 s)	6 mm	Copper	2 x M5 studs	0.5 A	150 A
201640	-	12 V	Black	600 A (5 s)	6 mm	Copper	2 x M5 studs	0.7 A	Permanent use
201660	-	24 V	Black	600 A (5 s)	6 mm	Copper	2 x M5 studs	0.4 A	Permanent use
202540	-	24 V	Black	600 A (5 s)	6 mm	Copper	2 x M5 studs	0.4 A	Permanent use

On request: specific technical demand can be studied

PUSH BUTTONS AND SWITCHES

SWITCH AND BUTTON



PUSH AND BUTTON
PUSH BUTTON

S700 SERIES



GLOBAL PRODUCT



GENERAL CHARACTERISTICS

IP65

+85 °C
-40 °C

PA6
Glass
reinforced

40g

Continuous rating 7 A

Overload until 25 A (10 s)

To use with:

S250 202301 - 202316 - 202317 - 202595 - 202597 - 202637
202639

PRODUCT SELECTION

P/N	NUMBER OF POLES	FINISH	AUXILIARY CIRCUIT
202170	Single pole	Red & Black	Normally open

On request: specific technical demand can be studied

ACCESSORIES (see «Spare parts» section)

CABLING KIT

S713 SERIES
4-Pin DIN connector

202326



PUSH AND BUTTON
ROTARY SWITCH

S701 SERIES



GLOBAL PRODUCT



GENERAL CHARACTERISTICS

IP65
IPX9K

+80 °C
-40 °C

PA6
Glass
reinforced

100g

Continuous rating 5 A

202556	To use with:
S260	202710 - 202712

250254	To use with:
S200	200358 - 200359 - 200439 - 200686 - 200735 - 200819 200820 - 200822 - 200824 - 201217 - 201245 - 201484 201497 - 201766 - 201926 - 202072 - 202136 - 202159
S220	203105 - 203106 - 203254 - 203255
S250	202310 - 202311 - 202319 - 202636 - 202664 - 202665 202698 - 202800 - 202976 - 203035

PRODUCT SELECTION

P/N	TYPE	FINISH	NUMBER OF POLES	ACCESSORIES	TERMINALS	CONNECTION
202556	Normally open	Red and black	Double pole	Yellow plate	Tin-plated copper	ISO 15170 / DIN 72585
202590	Inverser	Red and black	Double pole	Yellow plate	Tin-plated copper	ISO 15170 / DIN 72585
250254	Normally open	Red and black	Single pole	Yellow plate	Tin-plated copper	ISO 15170 / DIN 72585

On request: specific technical demand can be studied

ACCESSORIES (see «Spare parts» section)

CABLING KIT

S713 SERIES 202326
4-Pin DIN connector

BATTERY SWITCH
ELECTRICAL CONTROL

BATTERY SWITCH
MANUAL CONTROL

POWER RELAY

SWITCH AND BUTTON

ACCESSORIES AND
SPARE PARTS



PUSH AND BUTTON SNAP ACTION SWITCH

S702 SERIES



GLOBAL PRODUCT



GENERAL CHARACTERISTICS

IP66

+85 °C
-30 °C

PPO
Glass
reinforced

150g

M8

Continuous rating 130 A

Overload until 500 A (10 s)

To use with:

S200 200358 - 200359 - 200439 - 200686 - 200735 - 200819
200820 - 200822 - 200824 - 201217 - 201245 - 201484
201497 - 201766 - 201926 - 202072 - 202136 - 202159

PRODUCT SELECTION

P/N	MARKING	FINISH	NUMBER OF POLES	ACCESSORIES
201601	French	Red and black	Single pole	Yellow plate
201859	English	Red and Black	Single pole	Yellow plate

On request: specific technical demand can be studied

ACCESSORIES AND SPARE PARTS

HANDLES AND ACCESSORIES 34

CONNECTION 41

BATTERY SWITCH
MANUAL CONTROL

BATTERY SWITCH
ELECTRICAL CONTROL

POWER RELAY

SWITCH AND BUTTON

ACCESSORIES AND
SPARE PARTS

ACCESSORIES AND SPARE PARTS

HANDLES AND ACCESSORIES

901 SERIES



HANDLE

200392

COLOR	MATERIAL
Red	Thermoplastic

To use with:

S190 200913



HANDLE

200700

COLOR	MATERIAL
Metallic	Zinc alloy

To use with:

S20 200061 - 200801 - 202740



HANDLE

200929

COLOR	MATERIAL
Red	Thermoplastic

To use with:

S100 200004 - 200011 - 201148

901 SERIES

BATTERY SWITCH
ELECTRICAL CONTROL

BATTERY SWITCH
MANUAL CONTROL

POWER RELAY

SWITCH AND BUTTON

ACCESSORIES AND
SPARE PARTS



HANDLE200993	
COLOR	MATERIAL
Metallic	Zinc alloy
To use with:	
S50200027	



HANDLE201134	
COLOR	MATERIAL
Red	Thermoplastic
To use with:	
S190201544	



HANDLE202474	
COLOR	MATERIAL
Red	Thermoplastic
To use with:	
S10201767 - 201768 - 201831 - 202365 - 203201	

ACCESSORIES AND SPARE PARTS

HANDLES AND ACCESSORIES

901 SERIES



HANDLE (with chain)

202633

COLOR	MATERIAL
Metallic	Zinc alloy

To use with:

S50 200028 - 201900



HANDLE

202841

COLOR	MATERIAL
Red	Zinc alloy

To use with:

S50 202500



HANDLE

REF	COLOR	MATERIAL
203085	Red	Thermoplastic
203252	Yellow	Thermoplastic

To use with:

S30 203250 - 203253 - 203260 - 203380

901 SERIES



HANDLE (with rubber protection) 203186

COLOR	MATERIAL
Metallic	Zinc alloy

To use with:	
S50	200027 - 200028 - 201900 - 202500
S20	203185

ACCESSORIES AND SPARE PARTS

HANDLES AND ACCESSORIES

900 SERIES



PROTECTION CAP

200802

COLOR	MATERIAL
Red	PVC

To use with:

S9	202373
S20	200061 - 200062 - 200801 - 202740 - 203185
S50	200027 - 200028 - 201900 - 202500



CHAIN

200894

COLOR	MATERIAL
Metallic	Zinc Alloy

To use with:

S10	201768 - 203201
S50	200028 - 201900 - 202500



RUBBER PROTECTION

201549

COLOR	MATERIAL
Black	PVC

To use with:

S20	200061 - 200062 - 200801 - 202740 - 203185
------------	--

ACCESSORIES AND SPARE PARTS

HANDLES AND ACCESSORIES

900 SERIES

BATTERY SWITCH
ELECTRICAL CONTROL

BATTERY SWITCH
MANUAL CONTROL

POWER RELAY

SWITCH AND BUTTON

ACCESSORIES AND
SPARE PARTS



PROTECTION CAPS (protection cap + rubber protection)

201898

COLOR	MATERIAL
Red	PVC

To use with:

S50 200027 - 200028 - 201900 - 202500



RUBBER PROTECTION

201899

COLOR	MATERIAL
Red	PVC

To use with:

S50 200027 - 200028 - 201900 - 202500



INSULATION PLATE

REF	COLOR	MATERIAL
203088	Black	PA66
203249	Yellow	PA66
203259	White	PA66

To use with:

S30 203250 - 203253 - 203260 - 203380

ACCESSORIES AND SPARE PARTS

HANDLES AND ACCESSORIES

900 SERIES



PROTECTION CAP

203243

COLOR	MATERIAL
Red	PVC

To use with:

S20 200061 - 200062 - 200801 - 202740 - 203185



RUBBER PROTECTION

500123

COLOR	MATERIAL
Red	PVC

To use with:

S20 200061 - 200062 - 200801 - 202740 - 203185

713 SERIES



CABLING KIT 202326
4-Pin DIN connector

- To use with:
- S700 202170
 - S701 202590 - 250254
 - S250 202323



CABLING KIT 250025
4-Pin Superseal connector

- To use with:
- S220 203105 - 203106 - 203254 - 203255



CABLING KIT 250333
4-Pin DIN connector

- To use with:
- S250 202319 - 202636

BATTERY SWITCH
ELECTRICAL CONTROL

BATTERY SWITCH
MANUAL CONTROL

POWER RELAY

SWITCH AND BUTTON

ACCESSORIES AND
SPARE PARTS

ACCESSORIES AND SPARE PARTS
CONNECTION

713 SERIES



CABLING KIT 250350
5-Pin Superseal connector

To use with:
S250 202323



CABLING KIT 250351
2-Pin Superseal connector

To use with:
S250 203035 - 202976



CABLING KIT 250352
7-Pin DIN connector

To use with:
S250 202595 - 202597 - 202637 - 202639
S260 202710 - 202712

900 SERIES



TERMINALS HEIGHTENED

200588

COLOR	MATERIAL
Metallic	Brass

To use with:
M10 terminals



TERMINALS INSULATION CAP

REF	COLOR	MATERIAL
201010	Red	PVC
202499	Black	PVC



To use with:
M10 terminals



BUSBAR

203213

TERMINALS SIZE	COLOR	MATERIAL
M8 x 3 (washers and nuts included)	Metallic	Tinned copper

To use with:
S220

AGRICULTURE





agriculture

viatemis.com



YOUR EMBEDDED MECHATRONIC SOLUTIONS



1601

Tel: 1.800.567.1041
Sales: 905.274.2555

Email: Sales@AccessControlSales.com
Web: www.AccessControlSales.com

ACCESS
CONTROL SALES

161 Lakeshore Rd. E.
Mississauga ON.
L5G 4T9